

Reducing Tee 130R

Product Description

Product Certification

UL Listed / FM Approved (EX 6624)

Material

ASTM A536

Threads

ASME B1.20.1

Pressure Rating

Test Pressure : 12.5 MPa

Max. Working Pressure : 2.5 MPa



Dimensions (in mm)

| Inch | mm | A | B | C |
|-------------------|----------|------|------|------|
| 1×1/2×1 | 25×15×25 | 38.1 | 38.1 | 35.5 |
| 1×3/4×1 | 25×20×25 | 38.1 | 38.1 | 36.8 |
| 1.1/4×1/2×1.1/4 | 32×15×32 | 44.5 | 44.5 | 38.9 |
| 1.1/4×1×1.1/4 | 32×25×32 | 44.5 | 44.5 | 42.4 |
| 1.1/2×1×1.1/2 | 40×25×40 | 49.3 | 49.3 | 45.7 |
| 1.1/2×1.1/4×1.1/2 | 40×32×40 | 49.3 | 49.3 | 47.8 |
| 2×1×2 | 50×25×50 | 57.2 | 57.2 | 51.3 |
| 2×1.1/4×2 | 50×32×50 | 57.2 | 57.2 | 53.3 |
| 2×1.1/2×2 | 50×40×50 | 57.2 | 57.2 | 54.8 |

