

## Reducing Tee 130R

### Product Description

#### Product Certification

UL Listed / FM Approved (EX 6624)

#### Material

ASTM A536

#### Threads

ASME B1.20.1

#### Pressure Rating

Test Pressure : 12.5 MPa

Max. Working Pressure : 2.5 MPa



### Dimensions (in mm)

Inch	mm	A	B	C
1.1/2x1x1/2	32x25x15	34	38.9	32
1.1/4x1x3/4	32x25x20	36.8	41.2	34.8
1.1/4x1x1.1/2	32x25x40	48	46	46
1.1/2x1x1/2	40x25x15	35.8	42.2	34
1.1/2x1x3/4	40x25x20	38.6	44.5	34.8
1.1/2x1x1.1/4	40x25x32	46.2	47.8	42.4
1.1/2x1.1/4x1/2	40x32x15	35.8	42.2	34
1.1/2x1.1/4x3/4	40x32x20	38.6	44.5	36.3
1.1/2x1.1/4x1	40x32x25	41.9	45.7	40.1
1.1/2x1.1/4x2	40x32x50	54.9	51.3	53.3
2x1x1.1/2	50x25x40	51.3	54.9	45.7
2x1.1/4x1	50x32x25	44	51	40
2x1.1/2x1/2	50x40x15	37.9	47.8	35.8
2x1.1/2x3/4	50x40x20	40.5	50	38.5
2x1.1/2x1	50x40x25	43.9	51.3	41.9
2x1.1/2x1.1/4	50x40x32	48.3	53.3	46.2

